

Teak 3

Code: 6813....

IMPREGNATING AND PROTECTIVE AGENT FOR TEAK

- REVIVES AND MAINTAINS NATURAL WOOD' S COLOUR
- PRESERVES WOOD
- PREVENTS AGING
- IMPREGNATES WOOD

CHARACTERISTICS

Teak 3 besides impregnating wood and reducing soil penetration, restores the natural oil content of wood. Furthermore Teak 3 enhances the natural colour of teak and makes the surfaces softer to touch.

TECNICAL DATA

Curing mechanism:	/
Specific weight:	0.80 ± 0,02 Kg/L
Solid By Volume:	
Flash Point:	+ 60 °C
Appearance:	/
Colour:	colourless, gold
Packaging:	0,50 / 2,5 litres

SURFACE PREPARATION

Apply Teak 3 to surfaces previously cleaned with Teak 1 and bleached with Teak 2.

APPLICATION

After the surface has been cleaned with Teak 1 and Teak 2 and after thorough drying, spread Teak 3 with a soft brush parallel to the fibres.

If the absorption of the product is very fast, a second coat should be applied. In this case, let the 1st coat dry for at least 30 minutes. At a temperature of 20° C the final drying time of the product is about 12 hours.

Teak 3

Code: 6813....

IMPREGNATING AND PROTECTIVE AGENT FOR TEAK

APPLICATION DATA

Drying time before use (20 °C):

Pot Life (20 °C):

Application temp. min/ max:

Hardener:

Mixing ratio by volume:

Mixing ratio by weight:

Thinner/Thinner for cleaning:

Wet film thickness per coat:

Dry film thickness per coat:

Theoretical coverage per coat:

Minimum covering time (20 °C):

Maximum covering time (20 °C):

Number of coats:

NOTES

SAFETY RULES

During application use gloves and avoid the contact of the product with the skin. Dispose the residual product properly, avoiding pollution. Keep out of the reach of children. Before use read the sections 7-8 of the Safety Data Sheet (MSDS). INSTRUCTIONS FOR THE SAFE BIOCIDAL PRODUCT DISPOSAL AND PACKAGING Empty packaging having contained biocidal products: empty packaging shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre. Packaging containing unused biocidal product: the unused product shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre, in this case it is forbidden to recycle packaging. Do not empty into drains and watercourses. The paint cans must not be stocked outside and must be stored at a temperature between 10 ° C and 35 ° C. Do not expose to the sun.

DISCLAIMER The information in this data sheet is based on accurate laboratory tests and practical experience, which guarantee the quality of the product if used according to our recommendations. The data contained herein are liable to modification as a result of continuous product development. We do not accept any liability arising from use not in accordance with our recommendations, unless authorized specifically by the Veneziani Technical Services. This edition annuls and replaces all previous issues.